



JP11207190A: CATALYST FOR PURIFICATION OF EXHAUST GAS AND ITS PRODUCTION

[View Images \(1 pages\)](#)

Country: JP Japan

Inventor(s): YAMADA KEIJI
TAKAMI AKIHIDE
IWAKUNI HIDEJI
KYOGOKU MAKOTO
OKAMOTO KENJI

Applicant(s): MAZDA MOTOR CORP



[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: Aug. 3, 1999 / Jan. 27, 1998

Application Number: JP1998000014053

IPC Class: B01J 037/02; B01D 053/94; B01J 021/16; B01J 023/10; B01J 023/34; B01J 023/76; B01J 029/12; F01N 003/08; F01N 003/28;

Abstract: **Problem to be solved:** To allow oxide of a metal such as Mn or Co to effectively exhibit catalytic action by adding a liq. mixture of a soln. of an NOx occluding material and a noble metal soln. to the oxide to support the noble metal and the NOx occluding material.
Solution: The catalyst has a honeycomb carrier 1 comprising cordierite excellent in heat resistance and two catalyst layers on the carrier 1. One of the catalyst layers is an inside catalyst layer 2 (lower catalyst layer) closer to the surface of the carrier 1 and the other is an outside catalyst layer 3 (upper catalyst layer) on the inside catalyst layer 2. In the inside catalyst layer 2, a noble metal as a catalyst metal and an NOx occluding material are supported on oxide of a metal selected from Mn, Co, Ti and Fe, alumina and CeO₂. In the outside catalyst layer 3, the noble metal and the NOx occluding material are supported on a zeolite layer. Platinum is particularly used as the noble metal. Barium is particularly used as the NOx occluding material.
COPYRIGHT: (C)1999,JPO

Foreign References: non

(No patents reference this one)

BEST AVAILABLE COPY